

3M™ Sun Control Window Film

Prestige 20

Clearly superior.

Benefits

- ▶ High visible light transmission providing excellent aesthetics
- ▶ Patented design that significantly reflects the sun’s energy in the Infrared range providing energy savings and enhanced comfort
- ▶ Low interior and exterior reflectivity enhances views while maintaining exterior appearance
- ▶ Non-metalized film with no signal interference and no chance for corrosion
- ▶ Helps extend the life of furnishings by significantly reducing harmful UV rays, the largest cause of fading
- ▶ Comprehensive warranty from 3M



3M Center, Building 235-2S-27
St. Paul, MN 55144-1000
3M.com/WindowFilm

3M is a trademark of 3M Company.
Used under license by 3M subsidiaries and affiliates. Please recycle.
Printed in the U.S.A. © 3M 2022.
All rights reserved. 98-0150-1138-4

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. **3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If the 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

LEED Certification	
Window films may be used toward the following LEED credits:	
▶ SS-8	▶ EA-1
▶ MR 1.1-1.2	▶ EQ-7.1
▶ MR 5.1-5.2	▶ EQ-7.2
▶ EQ-8.1-8.2	▶ ID

Glass Type (All 1/4")	Film Type	Visible Light			Total Solar Energy Rejected	60 degree gain Coefficient (G Value)	Solar Heat		U Value	Solar Heat Reduction	UV Light Reduction	Glare Reduction	Visible Light Gain Ratio
		Reflected (interior)	Reflected (exterior)	Transmitted			Normal						
Clear	PR20	5%	6%	21%	62%	65%	0.38	1.03	5.82	54%	99.9%	76%	0.6
Tinted	PR20	5%	5%	13%	64%	67%	0.36	1.03	5.82	43%	99.9%	76%	0.4
Double Clear	PR20	5%	13%	19%	50%	57%	0.51	0.47	2.70	28%	99.9%	77%	0.4
Double Tinted	PR20	5%	8%	11%	61%	68%	0.39	0.47	2.70	24%	99.9%	76%	0.3

Product Performance and Technical Data